

good **service**
makes the
DIFFERENCE



Aircraft Jack Maintenance & Proof Load Testing

Axle Jack Procedure

90 Day Maintenance Procedure:

- Check leaks including the following areas of the hydraulic system:
 - Hand pump (cylinder, fittings and seals)
 - Reservoir (welds and fittings)
- Inspect the Jack structure for corrosion, bending, cracking and excessive wear in the following areas:
 - Base plate
 - Mechanical extension
 - Hydraulic cylinder assembly
 - Retaining ring
 - Jack pads, nose and main gear adapters
 - Spacer blocks
- Check fluid levels with rams fully retracted to ensure proper level height
- Visually inspect extended rams for corrosion, foreign matter, excessive wear and leaks around ram seals. Remove any foreign matter.
- Check paint condition and touch-ups where necessary
- Actuate the hand pump and raise the ram to full extension.
- Apply water repellent that is Buna N compatible to the rams (DoAll, RPM, LPS or equivalent)
- Open release valve and verify that rams fully retract

12 Month Proof Load Testing Procedure: complete all of the above including:

- Check hydraulic fluid for contamination (dirt/water) drain and flush if required
- Capacity test (110% of jack's rated capacity)

[Contact us](#) to learn more about our on-site maintenance & proof load testing services.